



TEAK OIL

1. DESCRIPTION

Product Type

Xylazel Teak Oil is a mixture of natural resins and oils to nourish and feed wood. It is suitable for teak and similar woods.

Effectiveness

- Treated wood.
- Nourishes, feeds, seals and protects the natural beauty of exterior wood.
- It protects and enhances the wood by replacing the natural oils lost through weathering.
- It prevents greying.
- It protects the wood from stains and dust.
- Enhances the natural colour of the wood.

Advantages

- The long-lasting formulation protects wood from the harmful effects of weathering.
- Silky and natural finish.
- Easy to apply. Excellent penetration into timber.
- Easy maintenance, there is no need to sand, simple clean surface dirt apply more Teak Oil.

Surfaces

Suitable for use on all hardwoods including teak, iroko and exotic woods.

Apply in bare wood.

Colours

It provides a lightly honey finish in light woods.

Packaging: 750ml., 2,5 l. , 5 l. and 400ml. Spray (Spray only available in colour honey)

2. TECHNICAL DATA

Application: brush, roller or spray gun.

Cleaning equipment
Xylazel Thinner.

Density at 20°C: 0,875±0,005.

Dry: 3 - 4 hours.

Second coat: 30 minutes.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed.

Ensure surface is free from varnish or other finishes.

Application

Shake the tin well before use.

Apply liberally using a brush, roller or spray gun.

Teak Oil is easy to apply, simply apply and allow the oil to penetrate deep into wood for up to 20 minutes and wipe the surface dry with a clean, lint-free cloth. A second coat can be applied before the first coat is dry.

Allow to dry for 3 - 4 hours.

In case of doubt, try a test area first and allow to dry fully to ensure final appearance is acceptable.

Cleaning equipment

Xylazel Thinner or White Spirit.

4. OTHER INFORMATION

Do not store when room temperature is below 5°C or over 30°C.

Do not empty into drains or watercourses.

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

www.xylazel.com

