

Non-slip Decking Hardwood Floor Protector

1. DESCRIPTION OF THE PRODUCT

Specially formulated lazure for application on exterior wood decking, such as those around swimming pools or on decks where, being tropical hardwoods, traditional solvent-based coverings produce problems when it comes to drying, taking days or even, depending on the type of wood, do not dry completely.

XYLAZEL Sol Decking Non-slip Protector for Hardwood Floors is formulated with a combination of hybrid acrylic resins and polyurethane copolymers which provide it with the advantages of solvent-based (penetrability, uniformity, resistance to blocking) and water-based products (quick drying, tough weather protection, easy to apply).

It contains additives which provide a slightly granulated non-slip surface.

Characteristics

- Slightly granulated satin finish
- Quick dry, even on tropical wood
- Good adherence
- Anti-flaking
- Easy application and maintenance, no need to sand before subsequent applications
- Good uniformity and finish
- Durable and resists abrasion
- Resistant to tough weather conditions
- Low odour on application. Once dry, does not smell

- Water-based
- Contains active ingredients which superficially protect the applied product against blue stain fungi and mould (PT7)
- Class 3 Non-slip in compliance with UNEENV 12633-2003.
- Suitable for interiors with stairs or inclined surfaces with a slope of over 6%
- Suitable for exteriors with swimming pools or showers.

Fields of application

For the protection and decoration of exterior or interior decking, furniture and joinery, especially those manufactured with tropical woods such as iroko, teak, ipe, cumaru, acacia, autoclave-treated pine, etc.

Colours

Pine and teak

Packaging

750ml and 4L

2. TECHNICAL DATA

Density at 20° C: 1.02 ± 0.02 g/ml

Dry to the touch: approximately 1 hour, although this depends on the type of wood.

Dry for recoating: Around 3 hours, depending on the type of wood.

3. INSTRUCTIONS

Preparation of the surface

Apply on clean and dry surfaces. Remove flaked and loose oils, paints and varnishes, either by

stripping, scraping or sanding.

Protect non-resistant wood with Xylazel Primer against rotting, blue stain fungi and wood boring insects.

Coverage

Around 12 m²/l per coat.

Directions for use

The product comes ready to use. Stir and mix before and during application.

It can be applied with a brush, roller or sprayer. Apply the recommended amount, in two or more coats.

Do not apply at temperatures above 30°C nor with forecast rain in 48 hours.

Maintenance

For maintenance, there is no need to remove earlier coats of Xylazel Sol Decking.

Surfaces must be cleaned well before recoating. If necessary, apply pressurised water.

Cleaning of tools


Use soap and water.

4. SPECIAL INDICATIONS

Storage and handling

For storage and handling, please observe current regulations. Storage must be protected against freezing and high temperatures. Avoid spillage into watercourses. Follow the instructions on the product safety sheet.

Waste and empty packaging



xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

www.xylazel.com




should be treated in compliance with current legislation.

5. GENERAL CONDITIONS

These are general guidelines. They provide a description of our products and inform the user on their application and use. Given that the working conditions and associated materials are highly varied and different, it is understood that all individual cases cannot be covered here. If you have any doubts, we recommend you test the product first or else consult our Technical Assistance Service.

We answer for the invariably high quality of our products, in compliance with the provisions of our General Conditions for Sales and Supply.

There is a safety data sheet available on request.



xylazel, s.a.
APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRINO (PONTEVEDRA)
TEL.: +34 986 34 34 24
FAX: +34 986 34 64 17

