



DECKING

1. DESCRIPTION

Product Type

Xylazel Decking is a water based woodstain which provides long term protection and decoration to exterior woodwork. It is suitable for providing protection against UV rays, rain and humidity. Xylazel Decking gives a satin finish for all types of timber decking.

Advantages

- Quick Drying, even on tropical wood.
- Excellent adherence.
- Xylazel Decking protects wood from the sun's harmful UV rays, rain and humidity.
- Excellent hardness and abrasion resistance.
- Prevents WOOD SWELLING AND MOVEMENTS. It penetrates deep into wood without building a barrier. It allows wood to breathe.
- It is highly water repellent.
- It does not crack, peel or flake.
- It penetrates deep into wood without building a barrier.
- It enhances natural wood grain.
- Easy maintain, there is no need to sand.
- Low odour formula. Once dried, it does not smell.

Surfaces

Suitable for use on all types of timber decking including boards and tiles.
Suitable for use on all hardwoods including teak, iroko and exotic woods.

Colours

Teak and Pine.

Packaging

750 ml and 5 litres.

2. TECHNICAL DATA

Density at 20°C:

1.02±0.02g/mL.

Touch dry: 1 hour aprox.

Second coat: 3 hours aprox.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed. Sand to remove any loose wood fibres, paints or varnishes. It is deemed necessary to apply Xylazel Total to provide protection against decay and insects.

Covering capacity

12 m²/ L per coat.

Application

Xylazel Decking is ready to use, and can be applied by brush, roller or a spray gun. Apply one or two coats.

Maintenance

Easy maintenance, there is no need to sand, simply apply more Xylazel Decking when needed.

The period between maintenance application will vary and is dependent upon the degree of exposure, elevation, design of the component, quality of timber and original application.

The need for maintenance is indicated by lightening in colour and reduction in sheen as the coating erodes, and loss of water appearance.

Cleaning equipment

Water.

4. OTHER INFORMATION

Apply in accordance with the coverage guidelines otherwise product performance will be reduced. Do not apply if the room temperature is below 5°C or over 30°C during application and drying or in conditions of high humidity.

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Do not empty into drains or water courses. Some local authorities have special facilities for disposing of waste coatings.

5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n

36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

www.xylazel.com

