

Metallic Finish Gold Effect Spray

1.- Description

Type of product	Acrylic paint formulated with high quality resins and metallic inorganic pigments. Specially formulated to decorate all kinds of metal, glass and wood objects and structures. Provides a highly decorative finish for use in interiors. Gives surfaces a golden metallic effect.
Advantages	<ul style="list-style-type: none"> - Easy application and repainting - Excellent adherence - Hardens well - Long lasting shine - Quick drying
Fields of applications	Especially suitable for decorating all kinds of objects: Metal, Wood, Glass.

2.- Technical Data

Data	<p>Thickness of dry coat (ASTM D-823 ISO 2808): 10 microns per coat Theoretical coverage of the can: 3 m² Density (ASTM D-1475 ISO 2811): 1 Persoz Hardness (ASTM D-4366 ISO 1522): 210 ±15 seconds Hardness (ASTM D-3363 Pencil test): B Adherence (ASTM D-3359 ISO 2409): 0 B</p> <p>Application Conditions Minimum environmental Temp: 8°C Surface Temp: 5° C Max Humidity: 85% R.H.P. Paint resistance to heat: 150° C Can resistance to heat: < 50° C Propellant: GLP- HC C3-C4</p>
Drying time	2 h. approx.

3.- Instructions for Use

Preparation of surface	Surfaces must be dry, clean and free of dust and particles. Remove loose particles with a wire brush.
Application	Shake the can vigorously before use for around 1 minute. On iron and steel surfaces, apply Xylazel Metal Antirust Primer for better results. Hold the can vertically at a distance of 20 cm. Apply 2 or 3 thin coats to obtain the best results and avoid the formation of drops, leaving 5 minutes between coats. After use, turn the aerosol upside down and spray for a few seconds to flush out the valve and avoid obstruction of the diffuser. Testing is recommended if the compatibility of the surface is unknown.
Colour	Shiny metallic gold
Packaging	Spray 400 ml



4.- Special Indications

Do not apply on equipment connected to the mains and use in ventilated spaces. Do not use on surfaces in direct contact with food.

Close lid tightly after use and store in a cool, dry place. Protect from frost.

Do not store for prolonged periods at temperatures of over 35°C or below 5°C. For storage and handling, observe current legislation on storage and transport in regard to water systems and air.

Observe the safety indications. On using the product, take general protection and hygiene measures. Avoid spilling the product into water systems. The safety factsheet is available to professional users on request.

5.- General Conditions

The information provided is general and for guidance only. It describes our products and informs on application and use. Given that the working conditions and materials are varied and different, understandably all individual cases cannot be covered here. If there are any doubts, we recommend you conduct your own tests or consult our Technical Assistance Service.

We are answerable for the invariably high quality of our products, in compliance with the indications of our General Sales and Supply Conditions.