



CLASSIC WOODSTAIN

Matt / Satin

1. DESCRIPTION

Product Type

A Solvent-borne, semi-transparent matt or satin woodstain, available in a range of natural wood colours and colourless.

Effectiveness

- Xylazel Classic Woodstain provides protection against mould growth.
- It contains special resins that protect wood from the sun's harmful UV rays, rain and humidity.

Advantages

- RESISTS UV DEGRADATION.

Xylazel Classic Woodstain contains high quality, micro-fine, iron oxide pigments, to provide optimum protection against visible and ultraviolet light degradation and discolouration.

- WATER, RAIN and HUMIDITY REPELLENT.

- PREVENTS WOOD SWELLING AND MOVEMENTS. It penetrates deep into wood without building a barrier. It allows wood to breathe.

- PREVENTS BLUESTAIN FUNGI GROWTH. The active ingredients penetrate to give wood a long lasting protection.

- DECORATION and PROTECTION.

Its translucent and intermixable colours enhance natural wood grain.

- EASY MAINTENANCE. If you use Xylazel Classic Woodstain, there is no need to sand, simply apply more product when needed.

- EASY TO APPLY. It penetrates deep into wood. Excellent levelling properties.

- Low odour formula. Once dried, it does not smell.

Surfaces

Suitable for interior and exterior joinery, hardwoods, softwoods, cladding, beams, pillars, doors, frames, windows, fences, furniture and any wood piece.

Colours

Matt: colourless, sapelly, oak, chestnut, mahogany, walnut, teak, ebony, pine, palisandro, oregon pine, tea pine, wengue.

Satin: colourless, light oak, pine, sapelly, chestnut, walnut, teak, tea pine, wengue.

Packaging

375 ml, 750 ml, 2,5 litres and 5 litres.

2. TECHNICAL DATA

Density at 20°C:

Matt: 0.835 - 0.880 g/cm³

Satin: 0.900 - 0.930 g/cm³.

Touch dry: 6 hours.

Second coat: 12 hours.

Matt: (cat.A/f): 700 g/L (2007) - 700 g/L (2010). Máx VOCs 650 g/L.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed. Lightly sand to remove any loose wood fibres, paints or varnishes.

It is deemed necessary to apply Xylazel Wood Preserver to provide protection against decay and insects. In "oily" timbers such as teak and iroko, it is recommended to apply Xylazel Exotic Woods Primer.

Covering capacity

Matt: 220 to 140 mL/m², in 2 coats.

Satin: 140 mL/m², in two coats.

Application

Stir the product thoroughly.

Xylazel Classic Woodstain is ready to use, you should not dilute it with solvent or any other product. For the possible finish use a good quality brush, roller or a spray gun. Apply one or two coats. Always finish in the direction of the wood grain.

Maintenance

Easy maintenance, there is no need to sand, simply clean the surface and apply more Xylazel Classic Woodstain when needed.

The period between maintenance application will vary and is dependent upon the degree of exposure, elevation, design of the component, quality of timber and original application.

The need for maintenance is indicated by lightening in colour and reduction in sheen as the coating erodes, and loss of water appearance.

Cleaning equipment

Xylazel Thinner or White Spirit.

4. OTHER INFORMATION

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Do not apply if the room temperature is below 5°C or over 30°C during application and drying or in conditions of high humidity.

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Do not empty into drains or water courses. Some local authorities have special facilities for disposing of waste coatings.



xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n

36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

www.xylazel.com



5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



xylazel, s.a.
APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)
TEL.: +34 986 34 34 24
FAX: +34 986 34 64 17
www.xylazel.com





CLASSIC WOODSTAIN

Matt / Satin

1. DESCRIPTION

Product Type

A Solvent-borne, semi-transparent matt or satin woodstain, available in a range of natural wood colours and colourless.

Effectiveness

- Xylazel Classic Woodstain provides protection against mould growth.
- It contains special resins that protect wood from the sun's harmful UV rays, rain and humidity.

Advantages

- RESISTS UV DEGRADATION.

Xylazel Classic Woodstain contains high quality, micro-fine, iron oxide pigments, to provide optimum protection against visible and ultraviolet light degradation and discolouration.

- WATER, RAIN and HUMIDITY REPELLENT.

- PREVENTS WOOD SWELLING AND MOVEMENTS. It penetrates deep into wood without building a barrier. It allows wood to breathe.

- PREVENTS BLUESTAIN FUNGI GROWTH. The active ingredients penetrate to give wood a long lasting protection.

- DECORATION and PROTECTION.

Its translucent and intermixable colours enhance natural wood grain.

- EASY MAINTENANCE. If you use Xylazel Classic Woodstain, there is no need to sand, simply apply more product when needed.

- EASY TO APPLY. It penetrates deep into wood. Excellent levelling properties.

- Low odour formula. Once dried, it does not smell.

Surfaces

Suitable for interior and exterior joinery, hardwoods, softwoods, cladding, beams, pillars, doors, frames, windows, fences, furniture and any wood piece.

Colours

Matt: colourless, sapelly, oak, chestnut, mahogany, walnut, teak, ebony, pine, palisandro, oregon pine, tea pine, wengue.

Satin: colourless, light oak, pine, sapelly, chestnut, walnut, teak, tea pine, wengue.

Packaging

375 ml, 750 ml, 2,5 litres and 5 litres.

2. TECHNICAL DATA

Density at 20°C:

Matt: 0.835 - 0.880 g/cm³

Satin: 0.900 - 0.930 g/cm³.

Touch dry: 6 hours.

Second coat: 12 hours.

Matt: (cat.A/f): 700 g/L (2007) - 700 g/L (2010). Máx VOCs 650 g/L.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed. Lightly sand to remove any loose wood fibres, paints or varnishes.

It is deemed necessary to apply Xylazel Wood Preserver to provide protection against decay and insects. In "oily" timbers such as teak and iroko, it is recommended to apply Xylazel Exotic Woods Primer.

Covering capacity

Matt: 220 to 140 mL/m², in 2 coats.

Satin: 140 mL/m², in two coats.

Application

Stir the product thoroughly.

Xylazel Classic Woodstain is ready to use, you should not dilute it with solvent or any other product. For the possible finish use a good quality brush, roller or a spray gun. Apply one or two coats. Always finish in the direction of the wood grain.

Maintenance

Easy maintenance, there is no need to sand, simply clean the surface and apply more Xylazel Classic Woodstain when needed.

The period between maintenance application will vary and is dependent upon the degree of exposure, elevation, design of the component, quality of timber and original application.

The need for maintenance is indicated by lightening in colour and reduction in sheen as the coating erodes, and loss of water appearance.

Cleaning equipment

Xylazel Thinner or White Spirit.

4. OTHER INFORMATION

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Do not apply if the room temperature is below 5°C or over 30°C during application and drying or in conditions of high humidity.

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Do not empty into drains or water courses. Some local authorities have special facilities for disposing of waste coatings.



xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n

36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17


www.xylazel.com



5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



xylazel, s.a.
APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)
TEL.: +34 986 34 34 24
FAX: +34 986 34 64 17
www.xylazel.com

