

1.- Description

Type of product	Water-based varnish for baked clay and other porous surfaces Protects against stains, is water resistant and delivers the surface a smooth and silky feel with satin finish.
Advantages	<ul style="list-style-type: none"> - Water-based - Colourless - Increased transparency and levelling - Resistant to chemical products - Weatherproof - Resistant to scratches, water and stains - Easy to apply - Quick drying - Slight smell which disappears on drying - Does not scale or peel.
Fields of application	Unglazed baked clay tiles, porous ceramic tiles, rustic stoneware, brickwork, flowerpots... It is also used on stone, aged marble, concrete, artificial stone, prefabs in cement and, in general, any porous construction material. For interiors and exteriors.

2.- Technical Data

Data	Density at 20° C: 1.02 ± 0.02
Drying Time	Surface dries in around 2 hours. Wait 12 hours before walking on it.

3.- Instructions for Use

Preparation of the Surface	The surface must be clean, dry and free of dust, grease and salt residues. Prior products must be removed.
Application	<p>Apply generously with a brush. Roller or spray gun may also be used.</p> <p>Allow to dry for 4 hours before applying a second coat, in order to fill in all the pores. Further coats might have to be applied on highly absorbent surfaces. The tools are washed with water. Wait 12 hours before stepping on the varnished surface.</p> <p>On surfaces in new buildings, construction work must be allowed to dry for 30 days in the summer and 60 days in winter before applying the product. If the tiles were laid with fast-drying cement, 5 days are sufficient.</p>
Maintenance	When the covering begins to wear, just clean the surface and apply again.
Coverage	Depends on the porosity of the floor, 4 to 6 m ² /L
Packaging	750 ml and 4L
Colours	Colourless satin finish
Tools Cleaning	Soap and water.

4.- SPECIAL INDICATIONS

Close lid tightly after use and store in a cool, dry place. Protect from frost.

Do not store for prolonged periods at temperatures of over 45°C or below 5°C. For storage and handling, observe current legislation on storage and transport in regard to water systems and air.

Observe the safety indications. On using the product, take general protection and hygiene measures. Avoid spilling the product into water systems. The product is not hazardous in accordance with the Regulation on classification, packaging and labelling of hazardous products (R.D. 255/2003). The safety factsheet is available to professional users on request.

5.- GENERAL CONDITIONS

The information provided is general and for guidance only. It describes our products and informs on application and use. Given that the working conditions and materials are varied and different, understandably all individual cases cannot be covered here. If there are any doubts, we recommend you conduct your own tests or consult our Technical Assistance Service.

We are answerable for the invariably high quality of our products, in compliance with the indications of our General Sales and Supply Conditions.