

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** Xylazel  
C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Wood protector  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
xylazel, s.a.  
Gándaras de Prado – Budiño s/n  
36400 Porriño - Pontevedra - Spain  
Phone.: +34 986 343 424 -  
Fax: +34 986 346 240  
calidad@xylazel.com  
www.xylazel.com
- 1.4 Emergency telephone number:** +34 986 343 424 (07:00 - 15:00)

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) n° 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.  
Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400  
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410  
Asp. Tox. 1: Aspiration hazard, Category 1, H304  
Flam. Liq. 3: Flammable liquids, Category 3, H226
- 2.2 Label elements:**  
**CLP Regulation (EC) n° 1272/2008:**  
**Danger**
- 
- Hazard statements:**  
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways  
Flam. Liq. 3: H226 - Flammable liquid and vapour
- Precautionary statements:**  
P101: If medical advice is needed, have product container or label at hand  
P102: Keep out of reach of children  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.  
P501: Dispose of contents and / or their container according to the separated collection system used in your municipality
- Supplementary information:**  
EUH066: Repeated exposure may cause skin dryness or cracking  
EUH208: Contains 3-iodo-2-propynyl Butylcarbamate, Propiconazole. May produce an allergic reaction
- Substances that contribute to the classification**  
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics; Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w);  
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclics, <2% aromatics; Xylene (mixture of isomers)
- 2.3 Other hazards:**  
Non-applicable

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

- CONTINUED ON NEXT PAGE -

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER**



**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)**

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** Mixture composed of additives, aggregates, pigments and resins in solvents

**Components:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: Non-applicable EC: 918-481-9 Index: Non-applicable REACH: 01-2119457273-39-XXXX	<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b> Regulation 1272/2008 Asp. Tox. 1: H304 - Danger	Self-classified <b>50 - &lt;75 %</b>
CAS: Non-applicable EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35-XXXX	<b>Hydrocarbons, C9, aromatics (Benzene &lt; 0.1 % w/w)</b> Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336 - Danger	Self-classified <b>10 - &lt;25 %</b>
CAS: Non-applicable EC: 919-857-5 Index: Non-applicable REACH: 01-2119463258-33-XXXX	<b>Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclics, &lt;2% aromatics</b> Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336 - Danger	Self-classified <b>2,5 - &lt;10 %</b>
CAS: 60207-90-1 EC: 262-104-4 Index: 613-205-00-0 REACH: Non-applicable	<b>Propiconazole</b> Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1: H317 - Warning	ATP CLP00 <b>&lt;1 %</b>
CAS: 55406-53-6 EC: 259-627-5 Index: 616-212-00-7 REACH: Non-applicable	<b>3-iodo-2-propynyl Butylcarbamate</b> Regulation 1272/2008 Acute Tox. 3: H331; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Sens. 1: H317; STOT RE 1: H372 - Danger	ATP ATP06 <b>&lt;1 %</b>
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene (mixture of isomers)</b> Regulation 1272/2008 Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified <b>&lt;1 %</b>
CAS: 52315-07-8 EC: 257-842-9 Index: 607-422-00-X REACH: Non-applicable	<b>a-cypermethrin (ISO)</b> Regulation 1272/2008 Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; STOT RE 2: H373; STOT SE 3: H335 - Danger	ATP ATP01 <b>&lt;1 %</b>

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

This product is not classified as hazardous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

**4.2 Most important symptoms and effects, both acute and delayed:**

- CONTINUED ON NEXT PAGE -

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER****SECTION 4: FIRST AID MEASURES (continued)**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER**



**SECTION 7: HANDLING AND STORAGE (continued)**

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 35 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the work environment

Identification		Environmental limits	
Xylene (mixture of isomers)	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
CAS: 1330-20-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
EC: 215-535-7	Year	2015	

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	150 mg/m <sup>3</sup>	Non-applicable
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 919-857-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	300 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1500 mg/m <sup>3</sup>	Non-applicable
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32 mg/m <sup>3</sup>	Non-applicable
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 919-857-5	Oral	Non-applicable	Non-applicable	300 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	300 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	900 mg/m <sup>3</sup>	Non-applicable

- CONTINUED ON NEXT PAGE -

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene (mixture of isomers)	Oral	Non-applicable	Non-applicable	1.6 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	14.8 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification				
Xylene (mixture of isomers)	STP	6.58 mg/L	Fresh water	0.327 mg/L
CAS: 1330-20-7	Soil	2.31 mg/kg	Marine water	0.327 mg/L
EC: 215-535-7	Intermittent	0.327 mg/L	Sediment (Fresh water)	12.46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12.46 mg/kg

**8.2 Exposure controls:**

**A.- General security and hygiene measures in the work place**

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

**C.- Specific protection for the hands**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CE CAT III	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

**D.- Ocular and facial protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face mask	CE CAT II	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Bodily protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CE CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CE CAT III	EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.



**F.- Additional emergency measures**

It is not necessary to take additional emergency measures.

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	85.6 % weight
V.O.C. density at 20 °C:	709.65 kg/m <sup>3</sup> (709.65 g/L)
Average carbon number:	9.08
Average molecular weight:	129.8 g/mol

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Not available
Color:	Colourless
Odor:	Characteristic

**Volatility:**

Boiling point at atmospheric pressure:	194 °C
Vapour pressure at 20 °C:	200 Pa
Vapour pressure at 50 °C:	1214 Pa (1 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	816 - 842 kg/m <sup>3</sup>
Relative density at 20 °C:	0.816 - 0.842
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	<20.5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

**Flammability:**

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER**



**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Flash Point:	54 °C
Autoignition temperature:	265 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

**9.2 Other information:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER**



**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification		Acute toxicity	Genus
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	LD50 oral	5100 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	>2000 mg/kg	
EC: 919-857-5	LC50 inhalation	>20 mg/L (4 h)	
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w)	LD50 oral	>2000 mg/kg	
CAS: Non-applicable	LD50 dermal	>2000 mg/kg	
EC: 918-668-5	LC50 inhalation	>20 mg/L (4 h)	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	LD50 oral	>2000 mg/kg	
CAS: Non-applicable	LD50 dermal	>2000 mg/kg	
EC: 918-481-9	LC50 inhalation	>20 mg/L (4 h)	
3-iodo-2-propynyl Butylcarbamate	LD50 oral	1100 mg/kg	Rat
CAS: 55406-53-6	LD50 dermal	2100 mg/kg (ATEi)	Rabbit
EC: 259-627-5	LC50 inhalation	3 mg/L (4 h) (ATEi)	
Propiconazole	LD50 oral	1517 mg/kg	Rat
CAS: 60207-90-1	LD50 dermal	>2000 mg/kg	
EC: 262-104-4	LC50 inhalation	>20 mg/L	
Xylene (mixture of isomers)	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation	>20 mg/L	
a-cypermethrin (ISO)	LD50 oral	>2000 mg/kg	
CAS: 52315-07-8	LD50 dermal	>2000 mg/kg	
EC: 257-842-9	LC50 inhalation	>5 mg/L	

**Acute Toxicity Estimate (ATE mix):**

	ATE mix	Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	500 mg/L (4 h) (Calculation method)	0 %

- CONTINUED ON NEXT PAGE -



**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER**



**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

Identification	Acute toxicity	Species	Genus
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w)	LC50 1 - 10 mg/L (96 h)		Fish
CAS: Non-applicable	EC50 1 - 10 mg/L		Crustacean
EC: 918-668-5	EC50 1 - 10 mg/L		Algae
Propiconazole	LC50 5.3 mg/L (96 h)	Salmo gairdneri	Fish
CAS: 60207-90-1	EC50 10.2 mg/L (48 h)	Daphnia magna	Crustacean
EC: 262-104-4	EC50 0.76 mg/L (72 h)	Scenedesmus subspicatus	Algae
3-iodo-2-propynyl Butylcarbamate	LC50 0.07 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 55406-53-6	EC50 0.09 mg/L (96 h)	Mysidopsis bahia	Crustacean
EC: 259-627-5	EC50 0.05 mg/L (72 h)	Scenedesmus subspicatus	Algae
Xylene (mixture of isomers)	LC50 13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50 0.6 mg/L (96 h)	Gammarus lacustris	Crustacean
EC: 215-535-7	EC50 10 mg/L (72 h)	Skeletonema costatum	Algae
a-cypermethrin (ISO)	LC50 Non-applicable		
CAS: 52315-07-8	EC50 0.001 mg/L (48 h)	Daphnia magna	Crustacean
EC: 257-842-9	EC50 Non-applicable		

**12.2 Persistence and degradability:**

Identification	Degradability	Biodegradability
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	BOD5 Non-applicable	Concentration Non-applicable
CAS: Non-applicable	COD Non-applicable	Period 28 days
EC: 919-857-5	BOD5/COD Non-applicable	% Biodegradable 80 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential
Propiconazole	BCF 146
CAS: 60207-90-1	Pow Log 3.72
EC: 262-104-4	Potential High
3-iodo-2-propynyl Butylcarbamate	BCF 36
CAS: 55406-53-6	Pow Log 2.4
EC: 259-627-5	Potential Moderate
Xylene (mixture of isomers)	BCF 9
CAS: 1330-20-7	Pow Log 2.77
EC: 215-535-7	Potential Low
a-cypermethrin (ISO)	BCF 420
CAS: 52315-07-8	Pow Log 6.6
EC: 257-842-9	Potential High

**12.4 Mobility in soil:**

Identification	Absorption/desorption	Volatility
a-cypermethrin (ISO)	Koc 5800	Henry 4.256E-2 Pa·m <sup>3</sup> /mol
CAS: 52315-07-8	Conclusion Immobile	Dry soil No
EC: 257-842-9	Surface tension Non-applicable	Moist soil No

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)

- CONTINUED ON NEXT PAGE -

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER****SECTION 13: DISPOSAL CONSIDERATIONS (continued)**

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION****Transport of dangerous goods by land:**

With regard to ADR 2015 and RID 2015:

	<b>14.1 UN number:</b>	UN1306
	<b>14.2 UN proper shipping name:</b>	WOOD PRESERVATIVES, LIQUID
	<b>14.3 Transport hazard class(es):</b>	3
	Labels:	3
	<b>14.4 Packing group:</b>	III
	<b>14.5 Dangerous for the environment:</b>	Yes
	<b>14.6 Special precautions for user</b>	
Special regulations:	640E	
Tunnel restriction code:	D/E	
Physico-Chemical properties:	see section 9	
Limited quantities:	5 L	
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable	

**Transport of dangerous goods by sea:**

With regard to IMDG 37-14:

	<b>14.1 UN number:</b>	UN1306
	<b>14.2 UN proper shipping name:</b>	WOOD PRESERVATIVES, LIQUID
	<b>14.3 Transport hazard class(es):</b>	3
	Labels:	3
	<b>14.4 Packing group:</b>	III
	<b>14.5 Dangerous for the environment:</b>	Yes
	<b>14.6 Special precautions for user</b>	
Special regulations:	223, 955	
EmS Codes:	F-E, S-D	
Physico-Chemical properties:	see section 9	
Limited quantities:	5 L	
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable	

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2015:

- CONTINUED ON NEXT PAGE -

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER****SECTION 14: TRANSPORT INFORMATION (continued)**

<b>14.1 UN number:</b>	UN1306
<b>14.2 UN proper shipping name:</b>	WOOD PRESERVATIVES, LIQUID
<b>14.3 Transport hazard class(es):</b>	3
Labels:	3
<b>14.4 Packing group:</b>	III
<b>14.5 Dangerous for the environment:</b>	Yes
<b>14.6 Special precautions for user</b>	
Physico-Chemical properties:	see section 9
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Composition of the active ingredients (Regulation (EU) No 528/2012): 3-iodo-2-propynyl Butylcarbamate (0.6%); Propiconazole (0.6%); a-cypermethrin (ISO) (0.05%)

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Propiconazole (Product-type 7, 8, 9) ; 3-iodo-2-propynyl Butylcarbamate (Product-type 6, 7, 8, 9, 10, 13) ; a-cypermethrin (ISO) (Product-type 8, 18)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION****Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EU) N° 453/2010, Regulation (EC) N° 2015/830)

**Modifications related to the previous security card which concerns the ways of managing risks. :****COMPOSITION/INFORMATION ON INGREDIENTS:**

- Removed Content
- Tebuconazole (ISO) (107534-96-3)

**Texts of the legislative phrases mentioned in section 2:**

- CONTINUED ON NEXT PAGE -

**Xylazel**  
**C12003 - XYLAZEL WOOD PRESERVATIVE PRIMER****SECTION 16: OTHER INFORMATION (continued)**

H400: Very toxic to aquatic life  
 H410: Very toxic to aquatic life with long lasting effects  
 H304: May be fatal if swallowed and enters airways  
 H226: Flammable liquid and vapour

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) n° 1272/2008:**

Acute Tox. 3: H301 - Toxic if swallowed  
 Acute Tox. 3: H331 - Toxic if inhaled  
 Acute Tox. 4: H302 - Harmful if swallowed  
 Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled  
 Aquatic Acute 1: H400 - Very toxic to aquatic life  
 Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects  
 Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects  
 Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways  
 Eye Dam. 1: H318 - Causes serious eye damage  
 Eye Irrit. 2: H319 - Causes serious eye irritation  
 Flam. Liq. 3: H226 - Flammable liquid and vapour  
 Skin Irrit. 2: H315 - Causes skin irritation  
 Skin Sens. 1: H317 - May cause an allergic skin reaction  
 STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure  
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)  
 STOT SE 3: H335 - May cause respiratory irritation  
 STOT SE 3: H336 - May cause drowsiness or dizziness

**Classification procedure:**

Aquatic Acute 1: Calculation method  
 Aquatic Chronic 1: Calculation method  
 Asp. Tox. 1: Calculation method  
 Flam. Liq. 3: Calculation method (2.6.4.3)

**Advice related to training:**

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://esis.jrc.ec.europa.eu>  
<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
 IMDG: International maritime dangerous goods code  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organisation  
 COD: Chemical Oxygen Demand  
 BOD5: 5-day biochemical oxygen demand  
 BCF: Bioconcentration factor  
 LD50: Lethal Dose 50  
 CL50: Lethal Concentration 50  
 EC50: Effective concentration 50  
 Log-POW: Octanol–water partition coefficient  
 Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -